

Portland Cliff

12x24 Color Body Glazed Porcelain

mosaic
Products. Design. Solutions.



03PDC011224




03PDC021224



03PDC031224



2x4 Stacked Mosaic



Barrel Mosaic



03PDC041224



03PDC051224



Tile: 12x24 - 24x48
Mosaics: 2x4 Stacked - 11x11 Barrel
Trim: 4x24 Bullnose - 6x12 Cove Base
Outdoor: 12x24

For more information
and images:



Technical Characteristics

Test Item	Test Method	Test Result
Breaking Strength	ASTM C648	> 450 lbf
Bond Strength	ASTM C482	> 200 psi
Chemical Resistance	ASTM C650	Unaffected
Frost Resistance	ASTM C1026	Resistant
Water Absorption	ASTM C373	< 0.50%
Scratch Hardness	Mohs Scale	7
DCOF	AcuTest	0.42-0.52 (Unpolished); 0.60-0.70 (Exterior)

Nominal Size	Actual Size	Thickness	Finish	Rectified
12" x 24"	11.69" x 23.5"	9.5 mm	Upolished or Exterior	Yes
24" x 48"	23.5" x 47.13"	10.5 mm	Upolished	Yes
2" x 4" Stacked Mosaic	11.69" x 11.69"	9.5 mm	Upolished	-
11" x 11" Barrel Mosaic	10.55" x 10.63"	9.5 mm	Upolished	-
4" x 24" Bullnose	3.81" x 23.5"	9.5 mm	Upolished	-
6" x 12" Cove Base	5.91" x 11.69"	9.5 mm	Upolished	-

Installation Note: The TCNA recommends rectangular shape tile be installed with maximum of 33% offset in order to resolve any possible lippage from one tile to the next.

