

Log

8x48 Glazed Porcelain

mosaic 
Products. Design. Solutions.



15LOGICO848



15LOGAMB848



QuickSHIP

Tile: 8x48

Mosaic: N/A

Trim: N/A

For more information
and images:



Made in Italy
v.1-26



Technical Characteristics

Specs	Test Method	Industry Standard	Test Result
Water Absorption	ASTM C373	Max \leq 0.5%	\leq 0.5%
Breaking Strength	ISO 10545-4	S \geq 1300 N	S \geq 1500 N
Bending Resistance	ISO 10545-4	R \geq 35 N/mm ²	R \geq 40 N/mm²
Impact Resistance	ISO 10545-5	As Reported	\geq 0.55
Mohs Hardness	EN 101	As Reported	MOHS 6
Deep Abrasion Resistance	ISO 10545-6	\leq 175 mm ³	\leq 150 mm ³
Thermal Shock Resistance	ISO 10545-9	As Reported	Resistant
Frost Resistance	ISO 10545-12	As Reported	Resistant
Reaction to Fire	-	Class A1 or A1fl	A1 - A1_{fl}
Chemical Resistance	ISO 10545-13	Min B Class	A
Stain Resistance	ISO 10545-14	As Reported	5
Dynamic Coefficient of Friction (DCOF)	ANSI A.137.1	Requires a min. value of 0.42 for level interior space expected to be walked upon when wet	\geq 0.50 Wet

Nominal Size	Actual Size	Thickness	Finish	Rectified
8" x 48"	7.87" x 47.24"	9 mm	Matte Sensitech	Yes

All tile is subject to variations in technical specifications and performance due to the inherent variables in the raw materials and production process. It is understood that test results on a particular product may vary slightly from tile to tile and from test to test. Test results are not guarantees of minimum or maximum thresholds of performance.

Installation Note: Due to its linear plank shape, this material requires particular care when it comes to installation. The tile will look its best when offset is less than 33%. The staggered installation will minimize lippage which is common in tiles of this format. No claim will be honored after installation.



For your convenience, select products are stocked in our Central Service Center.