

Marvel Epic

24x48 Glazed Porcelain

mosaic 
Products. Design. Solutions.



15EPITWH2448 (matte)



15EPITWH2448P (polished)



QuickSHIP (COMING SOON)

Tile: 24x48

Mosaic: N/A

Trim: N/A

For more information
and images:



Made in Italy
v.1-26

Technical Characteristics

Specs	Test Method	Industry Standard	Test Result	
Water Absorption	ASTM C373	Max $\leq 0.5\%$	$\leq 0.5\%$	
Breaking Strength	ISO 10545-4	$S \geq 1300$ N	$S \geq 1500$ N	
Bending Resistance	ISO 10545-4	$R \geq 35$ N/mm ²	$R \geq 40$ N/mm ²	
Impact Resistance	ISO 10545-5	As Reported	≥ 0.55	
Mohs Hardness	EN 101	As Reported	MOHS 6	
Deep Abrasion Resistance	ISO 10545-6	≤ 175 mm ³	≤ 150 mm ³	
Thermal Shock Resistance	ISO 10545-9	As Reported	Resistant	
Frost Resistance	ISO 10545-12	As Reported	Resistant	
Reaction to Fire	-	Class A1 or A1fl	A1 - A1 _{fl}	
Chemical Resistance	ISO 10545-13	Min B Class	A	
Stain Resistance	ISO 10545-14	As Reported	5	
			Matte	Polished
Dynamic Coefficient of Friction (DCOF)	ANSI A.137.1	Requires a min. value of 0.42 for level interior space expected to be walked upon when wet	≥ 0.50 Wet	≥ 0.42 Wet

Nominal Size	Actual Size	Thickness	Finish	Rectified
24" x 48"	23.62" x 47.24"	9 mm	Matte Sensitech or Polished	Yes

All tile is subject to variations in technical specifications and performance due to the inherent variables in the raw materials and production process. It is understood that test results on a particular product may vary slightly from tile to tile and from test to test. Test results are not guarantees of minimum or maximum thresholds of performance.



For your convenience, select products are stocked in our Central Service Center.