

# Marvel T

12x24 Glazed Porcelain

**mosaic**   
Products. Design. Solutions.



15MATHWH1224



15MATHSA1224




15MATNWH1224



15MATHWH2M



15MATHSA2M



15MATNWH2M



QuickSHIP (MOSAIC COMING SOON)

Tile: 12x24

Mosaic: 2x2

Trim: N/A

For more information  
and images:



Made in Italy  
v.1-26



### Technical Characteristics

Specs	Test Method	Industry Standard	Test Result
<b>Water Absorption</b>	ASTM C373	Max $\leq$ 0.5%	$\leq$ 0.5%
<b>Breaking Strength</b>	ISO 10545-4	S $\geq$ 1300 N	<b>S <math>\geq</math> 1500 N</b>
<b>Bending Resistance</b>	ISO 10545-4	R $\geq$ 35 N/mm <sup>2</sup>	<b>R <math>\geq</math> 40 N/mm<sup>2</sup></b>
<b>Impact Resistance</b>	ISO 10545-5	As Reported	$\geq$ 0.55
<b>Mohs Hardness</b>	EN 101	As Reported	<b>MOHS 6</b>
<b>Deep Abrasion Resistance</b>	ISO 10545-6	$\leq$ 175 mm <sup>3</sup>	$\leq$ 150 mm <sup>3</sup>
<b>Thermal Shock Resistance</b>	ISO 10545-9	As Reported	<b>Resistant</b>
<b>Frost Resistance</b>	ISO 10545-12	As Reported	<b>Resistant</b>
<b>Reaction to Fire</b>	-	Class A1 or A1fl	<b>A1 - A1<sub>fl</sub></b>
<b>Chemical Resistance</b>	ISO 10545-13	Min B Class	<b>A</b>
<b>Stain Resistance</b>	ISO 10545-14	As Reported	<b>5</b>
<b>Dynamic Coefficient of Friction (DCOF)</b>	ANSI A.137.1	Requires a min. value of 0.42 for level interior space expected to be walked upon when wet	<b><math>\geq</math> 0.50 Wet</b>

Nominal Size	Actual Size	Thickness	Finish	Rectified
12" x 24"	11.75" x 23.625"	9 mm	Matte Sensitech	Yes
2" x 2"	11.75" x 11.75"	9 mm	Matte Sensitech	-

All tile is subject to variations in technical specifications and performance due to the inherent variables in the raw materials and production process. It is understood that test results on a particular product may vary slightly from tile to tile and from test to test. Test results are not guarantees of minimum or maximum thresholds of performance.



For your convenience, select products are stocked in our Central Service Center.