





Plywood Subfloor Recess System

A bracket system designed to provide the necessary depth to install a true, zero-entry curbless shower on a wood subfloor.

FEATURES AND BENEFITS

- (Rapid Recess doesn't interfere with plumbing or other obstacles between the joists)
- * Floor height within the shower area is recessed 11/16" inch
- * Suitable for 25 square feet or less recommended sizes are 5' x 5' or 4' x 6'
- * No framing ledger boards or cross-bracing needed
- * Kits are available for point or linear drains and shower pans
- * Complies fully with ICC standards and codes
- passed the Robinson Test C627 for floor assemblies



1. Expose Expose the joists.



3. Recess Recess the subfloor.



Alexandria, VA | Chantilly, VA | Fairfax, VA | Richmond, VA | Virginia Beach, VA North Bethesda, MD* | Owings Mills, MD* | Greensboro, NC | Raleigh, NC

www.mosaictileco.com





Sell Sheet

* Installed from above the joists without the use of a 2x4 frame or compromising the structural integrity of the joists

* Kits are available for any kind, width or orientation of floor joists (joists parallel or perpendicular to shower entry)

* Rapid Recess brackets are made of sturdy 16 gauge galvanized steel and have undergone thorough testing and



2. Attach Attach the bracket system.



4. Finish Finish with shower pan and tile.

KIT OPTIONS BY DRAIN TYPE

FILLER AND SHIM KITS



22 Z-brackets (5" long)

with wings

with wings

8 M-brackets (48 3/8" long)

40 - #10 - 2 3/4" self-drilling reamers

160 - #10 - 1 5/8" self-drilling reamers

60 - #10 - 1 1/4" exterior wood screws

Used with a linear drain at the back wall. FLOOR

SHOWER ENTRY. Joist bay for drain is recessed 1"

below the top of the joists to accommodate depth

of the drain body. Remaining pan area is recessed


JOISTS MUST BE RUNNING PARALLEL TO THE

11/16". For showers up to 25 square feet.

30 Z brackets (5" long) 10 M brackets (48 3/8" long) 40 - #10 - 2 3/4" self-drilling reamers with wings 160 - #10 - 1 5/8" self-drilling reamers with wings 60 - #10 - 1 1/4" exterior wood screws



Used with a center point drain. Recommended to recess up to 25 square feet. Floor within the shower area is recessed 11/16". WORKS WITH JOISTS RUNNING PARALLEL OR PERPENDICULAR TO THE SHOWER ENTRY.




8 - #10 - 2 3/4" self-drilling reamers with wings 80 - #10 - 1 5/8" self-drilling reamers with wings



Used with a linear drain at the shower entry. Only the entry cutout in the plywood subfloor is recessed 11/16" to account for the drain depth. WORKS WITH JOISTS RUNNING PARALLEL OR PERPENDICULAR TO THE SHOWER ENTRY.

| Filler Kit-Small Item Number - RRFKS |
|---|
| Filler kit for linear drains 26" to 43" long |
| Fits a 25 square foot |

or less shower area



Item # - RRFKS

Kit includes: RRLDFS - small drain filler left (x1) RRRDFS - small drain filler right (x1) RRSS - 1/4" small shim (x2) RRW - sloped wedges (x3)

Used with a linear drain from 26" to 43" long. For shower areas up to 25 sq. ft.

Item # - RRFKL


Kit includes: RRLDFS - large drain filler left (x1) RRRDFS - large drain filler right (x1) RRSL - 1/4" large shim (x2) RRW - sloped wedges (x4)

Used with a linear drain 40" to 72" long. For showers areas up to 25 sq. ft.

Filler Kit-Large Item Number - RRFKL

Filler kit for linear drains 40" to 72" long

> Fits a 25 square foot or less shower area



Shim Kit

Item Number - RRSHIMK

Shim kit for 5/8" wood subfloors

Fits a 25 square foot or less shower area



Item # - RRSHIMK

Kit includes: HDPE Shims 5" long x 3/4"wide x 1/8" thick with double-sided tape (x60)

Used in bathrooms where 5/8" thick plywood exists and will be used.

Individual kit parts available. Please refer to Price List.